

BIS 230 (D)

Silicone-coated fiberglass sleeve



- high temperature resistance
- highly flexible

Specifications

Description	BIS 230 (D)
Material	fiberglass / silicone-coating
Operating temp. Min.	-60°C
Operating temp. Max.	+220°C (short term 250°C)
Dielectric strength	>4,0 kV / RT
Approvals / Standards	



Colours



TYPE	Inner diameter (D)	wallthickness (w) nom.	Packing unit
BIS 230 (D)	(mm)	(mm)	(Meter)
0,5	0,5 +/- 0,10	0,25 - 0,50	200
0,8	0,8 +/- 0,10	0,25 - 0,50	200
1,0	1,0 +/- 0,20	0,25 - 0,70	200
1,5	1,5 +/- 0,20	0,35 - 0,70	200
2,0	2,0 +/- 0,20	0,35 - 0,80	200
2,5	2,5 +/- 0,20	0,40 - 0,80	200
3,0	3,0 +/- 0,20	0,40 - 0,80	200
4,0	4,0 +/- 0,25	0,50 - 0,80	200
5,0	5,0 +/- 0,25	0,50 - 0,80	200
6,0	6,0 +/- 0,25	0,50 - 0,80	100
8,0	8,0 +/- 0,25	0,50 - 1,00	100
10,0	10,0 +/- 0,50	0,65 - 1,10	50
12,0	12,0 +/- 0,50	0,65 - 1,20	50
14,0	14,0 +/- 0,50	0,65 - 1,20	50
16,0	16,0 +/- 1,00	0,65 - 1,20	50
18,0	18,0 +/- 1,00	0,65 - 1,20	50
20,0	20,0 +/- 1,00	0,65 - 1,20	50