


BIS 230 UL (B)

UL-approved silicone-coated fiberglass sleeve




- flexible
- self-extinguishing
- UL-approved

Specifications

Description	BIS 230 UL (B)
Material	Fiberglass / silicone-rubber coating
Operating temp. Min.	-40°C
Operating temp. Max.	+180°C (short term +300°C)
Flammability	self-extinguishing
Dielectric strength	>5,0 kV / RT
Approvals / Standards	



Colours



TYPE	Inner diameter (D)	wallthickness (w) nom.	Packing unit
BIS 230 UL (B)	(mm)	(mm)	(Meter)
0,50	0,50 + 0,18	0,80 + 0,20	200
0,80	0,80 + 0,17	0,80 + 0,20	200
1,00	1,00 + 0,21	0,80 + 0,20	200
1,45	1,45 + 0,25	0,80 + 0,20	200
2,00	2,00 + 0,25	0,80 + 0,20	200
2,50	2,50 + 0,29	0,80 + 0,20	200
2,90	2,90 + 0,30	0,80 + 0,20	200
3,50	3,50 + 0,30	0,80 + 0,20	200
4,00	4,00 + 0,30	0,80 + 0,20	200
5,00	5,00 + 0,50	0,80 + 0,20	200
6,00	6,00 + 0,50	0,90 + 0,20	200
8,00	8,00 + 0,60	0,90 + 0,20	100
10,00	10,00 + 0,60	0,90 + 0,20	100
12,00	12,00 + 0,60	0,90 + 0,20	100
12,70	12,70 + 0,60	1,00 + 0,20	100
16,00	16,00 + 0,70	1,00 + 0,20	50
20,00	20,00 + 0,90	1,20 + 0,30	25
25,00	25,00 + 0,90	1,20 + 0,30	25