



- very flexible
- self-extinguishing
- fireproof
- good resistance against solvents
- halogen-free

Specifications	
Description	BIS ROH (D)
Material	fiberglass
Operating temp. Min.	-70°C
Operating temp. Max.	+550°C
Flammability	fireproof, self-extinguishing
Dielectric strength	>0,7 kV according to IEC 60684 (Ø)
	>0,6 kV according to IEC 60684 (min.)
	>0,9 kV according to UL 1441
Approvals / Standards	REACH compliant RoHS compliant

Colours

Technical drawing of the fiberglass sleeving cross-section, showing the inner diameter (D) and wall thickness (w).

TYPE	Inner diameter (D)	wallthickness (w) nom.	Packing unit
BIS ROH	(mm)	(mm)	(Meter)
0,5	0,5	0,20	400
0,8	0,8	0,20	400
1,0	1,0	0,20	300
1,5	1,5	0,30	300
2,0	2,0	0,30	300
2,5	2,5	0,30	300
3,0	3,0	0,30	200
3,5	3,5	0,30	200
4,0	4,0	0,30	200
5,0	5,0	0,40	200
6,0	6,0	0,40	100
7,0	7,0	0,40	100
8,0	8,0	0,40	100
9,0	9,0	0,40	100
10,0	10,0	0,40	100
12,0	12,0	0,40	100
14,0	14,0	0,50	100
16,0	16,0	0,50	100
18,0	18,0	0,50	100
20,0	20,0	0,50	50
22,0	22,0	0,50	50
25,0	25,0	0,50	50

custom and special sizes upon request