

BLVK

Schrumpfmuffen-Sets

Shrink-sleeve set

Eigenschaften / Properties

- Mittelwandig
 - Kleberbeschichtet
 - REACH / RoHS
-
- Medium wall
 - Adhesive lined
 - REACH / RoHS



Schrumpfmuffen-Sets

Shrink-sleeve set

Die Schrumpfmuffen-Sets BLVK sind perfekt für das Verbinden von mehradrigen Kabeln geeignet.

BLVK is a shrink-sleeve set perfect for consolidating multi-core cable and wire installations.

Norm / Standard



ROHS
COMPLIANT




REACH
COMPLIANT

Technische Daten / Technical data	
Beschreibung Description	BLVK
Material Material	Polyolefin Polyolefin
Schrumpfrate Shrink ratio	3:1
Einsatztemp. Min. Operating temp. Min.	-55°C
Einsatztemp. Max. Operating temp. Max.	+110°C
Schrumpftemperatur Min. Shrink temp. Min.	+120°C
Brennbarkeit Flammability	nicht flammgeschützt not flame-retardant
Längsschrumpf Longitudinal change	+/-10% max.
Durchschlagsfestigkeit Dielectric strength	>20,0 kV/mm
Kleberbeschichtung Adhesive coating	nein none

BLVK

Schrumpfmuffen-Sets

Shrink-sleeve set



Abmessungen
Dimensions

TYP	Leiterquerschnitt
	cable cross-section
BLVK 1,5 - 16 x 4	4 x 1,5 bis 4 x 16,0 mm ²
BLVK 1,5 - 16 x 5	5 x 1,5 bis 5 x 16,0 mm ²
BLVK 6,0 - 25 x 4	4 x 6,0 bis 4 x 25,0 mm ²
BLVK 16,0 - 50 x 4	4 x 16,0 bis 4 x 50,0 mm ²
BLVK 16,0 - 50 x 5	5 x 16,0 bis 5 x 50,0 mm ²
BLVK 25,0 - 95 x 4	4 x 25,0 bis 4 x 95,0 mm ²
BLVK 35,0 - 150 x 4	4 x 35,0 bis 4 x 150,0 mm ²
BLVK 95,0 - 300 x 4	4 x 95,0 bis 4 x 300,0 mm ²

Weitere Informationen
Further Information

Farben Colors	●