

## TH

Kabeldriller aus Polyamid 6.6

Polyamide 6.6 twist-lock cable ties

### Eigenschaften / Properties

- Kabeldriller
- REACh / RoHS
  
- Twist-lock cable ties
- REACh / RoHS



Kabeldriller aus Polyamid 6.6  
Polyamide 6.6 twist-lock cable ties

TH Kabeldriller zur schnellen und einfachen Kabelbündelung  
TH are twist-lock cable ties for quick and easy bundling of cables.

### Norm / Standard



Technische Daten / Technical data	
Beschreibung Description	TH
Material Material	PA 6.6 PA 6.6
Einsatztemp. Min. Operating temp. Min.	-40°C
Einsatztemp. Max. Operating temp. Max.	+85°C

# TH

Kabeldriller aus Polyamid 6.6

Polyamide 6.6 twist-lock cable ties

## Abmessungen Dimensions

TYP	Höhe Height (mm)	Bündlungsdurchmesser Bundling diameter (mm)
TH-D	28,4	7,6 - 10,2
TH-E	21,0	ca. 4,5
TH-F	25,2	5,1 - 7,6
TH-G	30,9	ca. 10,5
TH-H	35,1	13,0 - 16,5
TH-I	40,0	16,5 - 20,0

## Weitere Informationen Further Information

Farben Colors	