



- abriebfest

### Technische Daten

Beschreibung	BIS PA 12
Material	PA
Einsatztemp. Min.	-40°C
Einsatztemp. Max.	+90°C
Zulassungen / Normen	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 2px; text-align: center;">             REACH compliant         </div> <div style="border: 1px solid black; padding: 2px; text-align: center;">             RoHS compliant         </div> </div>

### Farben



TYP	Innendurchmesser (D)	Wandstärke (w) nom.	VPE
<b>BIS PA 12</b>	(mm)	(mm)	(Meter)
2,0 x 1,0	2,00 mm	1,00 mm	100 m
3,0 x 1,0	3,00 mm	1,00 mm	100 m
4,0 x 1,0	4,00 mm	1,00 mm	100 m
6,0 x 1,0	6,00 mm	1,00 mm	100 m
8,0 x 1,0	8,00 mm	1,00 mm	100 m
9,0 x 1,5	9,00 mm	1,50 mm	100 m
11,0 x 1,5	11,00 mm	1,50 mm	50 m
12,0 x 1,5	12,00 mm	1,50 mm	50 m
12,0 x 2,0	12,00 mm	2,00 mm	50 m
14,0 x 2,0	14,00 mm	2,00 mm	50 m
16,0 x 2,0	16,00 mm	2,00 mm	50 m

Auf Wunsch bedrucken und schneiden wir diesen Isolierschlauch nach Ihren Vorgaben.