

End caps

heat-shrinkable end caps



- adhesive-lined
- heat-shrink end cap

Specifications

Description	end caps
Material	Polyolefin
Shrink ratio	min. 3:1
Operating temp. Min.	-40°C
Operating temp. Max.	+125°C
Shrink temp. Min.	+120°C
Adhesive coating	yes
Approvals / Standards	



Colours



TYPE	on delivery	Recovered	
End caps	Ø (D) min. (mm)	Ø (d) max. (mm)	Max. cap length (mm)
3.0/1.0 x 22.0	3.00	1.00	22.00
10.0/3.0 x 35.0	10.00	3.00	35.00
12.0/4.0 x 40.0	12.00	4.00	40.00
14.0/4.5 x 58.0	14.00	4.50	58.00
15.0/4.5 x 45.0	15.00	4.50	45.00
20.0/6.0 x 63.0	20.00	6.00	63.00
25.0/8.0 x 55.0	25.00	8.00	55.00
25.0/8.5 x 70.0	25.00	8.50	70.00
40.0/14.5 x 102.0	40.00	14.50	102.00
55.0/26.0 x 125.0	55.00	26.00	125.00
63.0/24.0 x 118.0	63.00	24.00	118.00
75.0/26.0 x 145.0	75.00	26.00	145.00
75.0/32.0 x 120.0	75.00	32.00	120.00
85.0/36.0 x 140.0	85.00	36.00	140.00
100.0/50.0 x 160.0	100.00	50.00	160.00
106.0/45.0 x 164.0	106.00	45.00	164.00
120.0/45.0 x 160.0	120.00	45.00	160.00
120.0/57.0 x 155.0	120.00	57.00	155.00
145.0/60.0 x 165.0	145.00	60.00	165.00
154.0/60.0 x 165.0	154.00	60.00	165.00
200.0/90.0 x 160.0	200.00	90.00	160.00
230.0/125.0 x 220.0	230.00	125.00	220.00
300.0/125.0 x 220.0	300.00	125.00	220.00
400.0/204.0 x 220.0	400.00	204.00	220.00
500.0/204.0 x 220.0	500.00	204.00	220.00