



- dehnbar
- elastisch
- flammhemmend
- flexibel

## Technische Daten

Beschreibung	Gummitüllen
Material	Polychloropren Gummi
Einsatztemp. Min.	-30°C
Einsatztemp. Max.	+90°C
Zulassungen / Normen	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 5px; text-align: center;">             REACH compliant         </div> <div style="border: 1px solid black; padding: 5px; text-align: center;">             RoHS compliant         </div> </div>

## Farben



TYP	für Kabel	Innendurchmesser (D)	Länge	Wandstärke (w)
Gummitüllen	(mm)	(mm)	(mm)	(mm)
1,25 x 20	1,25 – 2,00	1,25	20,00	0,50
1,75 x 20	1,75 – 3,50	1,75	20,00	0,50
2,40 x 20	2,40 – 4,50	2,40	20,00	0,60
2,50 x 20	2,50 – 5,50	2,50	20,00	0,90
3,00 x 25	3,00 – 6,00	3,00	25,00	0,60
4,00 x 30	4,00 – 8,00	4,00	30,00	1,20
5,00 x 30	5,00 – 9,00	5,00	30,00	0,70
7,50 x 30	7,50 – 12,00	7,50	30,00	0,80
10,00 x 35	10,00 – 15,00	10,00	35,00	0,90
12,00 x 50	12,00 – 20,00	12,00	50,00	1,20
14,00 x 50	14,00 – 23,00	14,00	50,00	1,30
17,00 x 50	17,00 – 28,00	17,00	50,00	1,30

070/P750/01 1/05.2020