

BIS PVC GEW

Three-layer PVC hose with polyester thread insert



- extremely abrasion resistant
- very flexible
- smooth inside and out
- approved for Food Contact
- CE N° 10/2011

Specifications

Description	BIS PVC GEW
Material	Soft PVC
Operating temp. Min.	-20°C
Operating temp. Max.	+65°C
Approvals / Standards	



Colours



Inside diameter in mm	Wall thickness in mm	Operating pressure	Best print	Weight (gr/mm)
4	2	15	45	46
4	3	23	69	80
5	3	20	60	92
6	2,5	15	45	81
6	3	20	60	103
7	2	12	38	71
8	2,5	20	60	101
8	3	20	60	126
9	2	15	45	90
9	3	18	54	138
10	2,5	15	45	120
10	3	17	51	149
12	2,5	13	39	139
12	3	15	45	172
12	3,5	17	51	208
12	3	15	45	178
12,5	4,5	15	45	285
13	2	12	36	124
13	3	15	45	184
13	3,5	15	45	221
15	3	15	45	207
15	4	15	45	291
16	3	13	39	218
16	3,5	15	45	262
16	4	15	45	307
19	3,5	11	33	302
19	4	12	36	353
20	4	12	36	368
25	4	8	24	445
25	4,5	9	27	509
30	4	6	18	521
32	5	7	21	709

On request, we can print and cut this insulating tube according to your specifications.