

BPMW M

medium wall heat shrinkable polyolefin tubing
with mastic coating



- high electrical insulation
- high mechan. Protection
- medium wall
- mastic coated
- UV - resistant

Specifications

Description	BPMW M
Material	Polyolefin, medium wall
Shrinkage rate	3:1
Operating temp. min.	-35°C
Application temp. max.	+110°C
Shrinkage temperature Min.	+120°C
Tensile strength	≥ 12,0 MPa
Dielectric strength	≥ 12 kV/mm
Mastic coating	yes
Approvals / Standards	



Colours



TYPE	on delivery	after shrink		
BPMW M	Ø (D) min. (mm)	Ø (d) max. (mm)	Wall thickness (w) nom. (mm)	Packaging unit lengths (Meter)
30/6	30.0	6.00	2.50	1,00
33/8	33.0	8.00	2.60	1,00
40/12	40.0	12.00	2.60	1,00
55/16	55.0	16.00	2.70	1,00
75/22	75.0	22.00	3.00	1,00
95/25	95.0	25.00	3.20	1,00
115/34	115.0	34.00	3.50	1,00
140/42	140.0	42.00	3.30	1,00
160/50	160.0	50.00	3.30	1,00
180/58	180.0	58.00	3.30	1,00
205/65	205.0	65.00	2.50	1,00
235/65	235.0	65.00	3.70	1,00
265/75	265.0	75.00	3.80	1,00
300/75	300.0	75.00	3.80	1,00
350/100	350.0	100.00	4.30	1,00

On request, we can print and cut this heat-shrink tubing according to your specifications.